

VTCALCS for Matlab v1.0

Satrajit S. Ghosh satra@cns.bu.edu
Department of Cognitive and Neural Systems, Boston University
1999

This project was supported by the National Institute on Deafness and Other Communication Disorders (NIDCD) grant no. 1R29DC02852 to Prof. Frank Guenther guenther@cns.bu.edu, Department of Cognitive and Neural Systems, Boston University.

Contents

| | | |
|----------|--|------------|
| 1 | Acknowledgements | ii |
| 2 | Installation and User guide | iii |
| 2.1 | Downloading the program | iii |
| 2.2 | Installation | iii |
| 2.3 | Creating the mex files | iv |
| 2.4 | Using the program | iv |
| 2.4.1 | VT Calculation from Models | v |
| 2.4.2 | Changing Tract Configuration | v |
| 2.4.3 | Changing Physical Constants | v |
| 2.5 | Registered Trademarks | v |
| 3 | Known bugs and limitations | vi |
| 3.1 | 18.Oct.1999 | vi |
| A | Ranges of parameters | vii |
| A.1 | Physical constants | vii |
| A.2 | Uniform tube model parameters | vii |
| A.3 | Two tube model parameters | viii |
| A.4 | Three parameter model parameters | viii |
| A.5 | Articulator model parameters | viii |
| A.6 | Area function model parameters | viii |

Chapter 1

Acknowledgements

The underlying C code for generation of transfer functions and calculation of formants was written by Dr. Shinji Maeda (shinji@tsi.enst.fr), as part of a DOS program called VTCALCS.

The Matlab code for synthesis of vowels is part of a package called Track Draw, developed by Peter Assmann (assmann@utdallas.edu), and is available at the following URL: <http://www.utdallas.edu/~assmann/TRACKDRAW/trackdraw.html>

Chapter 2

Installation and User guide

2.1 Downloading the program

The program may be downloaded from the following URLs:

- <http://cns-web.bu.edu/satra/pub/vtcalcs.tgz> - for Unix
- <http://cns-web.bu.edu/satra/pub/vtcalcs.zip> - for MS Windows

2.2 Installation

The program can be installed in any directory. However the directory structure has to be maintained when unpacking.

1. Choose a directory for installation.
2. Copy the archived file into the directory.
3. Unzip the file while *maintaining the directory structure* . On UNIX systems one may use the command:

```
gunzip -c vtcalcs.tgz | tar xf
```

On Microsoft Windows systems either use an unzip program like Winzip or use pkunzip with the command:

```
pkunzip -d vtcalcs.zip
```

Most linux systems support the following command directly:

```
tar zxf vtcalcs.tgz
```

4. A directory called `vtcalcs` will be created with three subdirectories: `data`, `doc`, and `src`. `'data'` contains some necessary data files for running the program. `'doc'` contains this document. `'src'` contains the source code for compiling the mex functions.
5. If you are installing it on a system for which mex files have not been provided you need to create the mex files. This is described in the next section.

2.3 Creating the mex files

Creating the mex files requires that you have the Matlab compiler installed properly. For installing the Matlab compiler please refer to the documentation provided by Mathworks. On a MS Windows system this typically requires both the Matlab compiler as well as an additional compiler such as Microsoft Visual C++. Matlab v5.3 works fine however v5.2 and below is known to have problems on newer Linux systems and can result in segmentation violations. The following URL should help solve the problem:

<http://www.mathworks.com/support/solutions/v5/11129.shtml>

1. Start Matlab
2. Change to the source directory.
3. At the Matlab prompt type `Makefile('unix')` or `Makefile('windows')`. The function is case sensitive. If the compiler has been set up properly, the call should have created mex files for you specific platform.
4. Copy or move the mex files from the `'src'` directory to the `vtcalcs` directory. The files will have different extensions on different platforms. Some common platforms and extensions are listed below. Please refer to the compiler documentation for any other platforms.

| Platform | Extension |
|---------------|-----------|
| Windows 9x/NT | .dll |
| Linux | .mexlx |
| Solaris | .mex4 |

2.4 Using the program

To start the program open Matlab in the same directory where the m-file `vtcalcs.m` is. On Unix this can be accomplished by starting Matlab in the directory containing the file. On Windows one can change the directory from within Matlab by using the `'cd'` command. Once you are in the directory start the program by typing `vtcalcs` at the Matlab prompt. This launches the user interface (UI) for the program.

The UI has three menu options relevant to running the program. These are:

- VT Calculation
- Tract configuration
- Physical constants

2.4.1 VT Calculation from Models

The current version provides 5 different methods of calculating the transfer function. When selected it provides the user with the 5 options. The sixth option is currently not available and has been disabled. Choosing any of the other options opens a dialog box with rather intuitive controls. Most of the pushbuttons with numeric values on them popup dialogs which allow those values to be changed. Some push buttons toggle states and some perform a particular action (eg. synthesize). The sliders change values continuously. The allowable range of the values are provided in Appendix A.

2.4.2 Changing Tract Configuration

When this menu option is selected a dialog box with four pushbuttons pop up. Clicking on any of the buttons toggles its state and the current state is displayed on the button.

2.4.3 Changing Physical Constants

When this menu option is selected a dialog box with five pushbuttons pop up. Clicking on any of the buttons opens a dialog box where one can enter a new value. If no value is entered, the current value is retained. This dialog also keeps the entered value within range of possibly allowed values.

2.5 Registered Trademarks

- Matlab is a registered trademark of Mathworks Inc.
- Microsoft Visual C++, Microsoft Windows, MS Windows, Windows 9x/NT are registered trademarks of Microsoft corporation.
- Solaris is a registered trademark of Sun Microsystems.

Chapter 3

Known bugs and limitations

Although the current bugs do not hinder the functionality of the program directly, they will be removed in the next version. Some of these bugs, when removed, will add further possibilities to the program.

The following are the list of bugs as of 18.Oct.1999. Please send a mail to satra@cns.bu.edu for any new bugs.

3.1 18.Oct.1999

1. The program has to be started in the `vtcalcs` directory of the unzipped structure. No, directory change can be made while the program is running.
2. The popup dialog box vanishes behind the main figure.
3. `radimp-spec` is not currently read.
4. `saggital-to-area` does not work with a provided set of area functions.

Appendix A

Ranges of parameters

These parameters indicate the choices one can make from the graphical interface. Not all of them are necessary if any of the functions are to be embedded in a program.

A.1 Physical constants

| Parameter | Max | Min |
|-----------------|--------|--------|
| Air density | 1.5e-3 | 0.9e-3 |
| Sound velocity | 3.6e+4 | 3.3e+4 |
| Wall resistance | 2000 | 1000 |
| Wall mass | 2 | 1 |
| Wall compliance | 4e+5 | 2e+5 |

A.2 Uniform tube model parameters

| Parameter | Max | Min |
|----------------|-----|-----|
| Area | 15 | 0 |
| Length | 20 | 5 |
| Segments | 60 | 5 |
| Nasal coupling | 3 | 0 |

A.3 Two tube model parameters

| Parameter | Max | Min |
|----------------|-------|-----|
| A1 | 10 | 0 |
| x1 | 20-x2 | 0 |
| A2 | 10 | 0 |
| x2 | 20-x1 | 0 |
| Nasal coupling | 3 | 0 |

A.4 Three parameter model parameters

| Parameter | Max | Min |
|----------------|-----|-----|
| At | 8 | 0 |
| Xt | 13 | 3 |
| Al | 4 | 0 |
| Nasal coupling | 3 | 0 |

A.5 Articulator model parameters

| Parameter | Max | Min |
|------------------|-----|-----|
| All articulators | 3 | -3 |
| Vowel | 11 | 0 |
| Nasal coupling | 3 | 0 |

The vowels are as follows:

| | | | | | | | | | | | |
|------|----|----|----|----|----|----|----|----|----|----|----|
| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
| None | iy | ey | eh | ah | aa | ao | oh | uw | iw | ew | oe |

A.6 Area function model parameters

| Parameter | Max | Min |
|------------------------|-----|-----|
| No. of Sliders | 30 | 5 |
| Tube length | 20 | 5 |
| Internal tube segments | 60 | 5 |
| Nasal coupling | 3 | 0 |